




AMERICAN BEARING MFG.CORP.



6304ZZNR Bearing 2D drawings and 3D CAD models

20,000 mm x 52,000 mm x 15,000 mm NTN
6304ZZNR deep groove ball bearings

Bearing No. 6304ZZNR

| | |
|---------------------------------|--------------------------|
| Size | 20x52x15 mm |
| Bore Diameter | 20,000 mm |
| Outer Diameter | 52,000 mm |
| Width | 15,000 mm |
| d | 20,000 mm |
| D | 52,000 mm |
| B | 15,000 mm |
| C | 15,000 mm |
| Category | Single Row Ball Bearings |
| Inventory | 0.0 |
| Manufacturer Name | NTN |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0.143 |
| EAN | 4547359011258 |
| Product Group | B00308 |
| Enclosure | 2 Metal Shields |
| Precision Class | ABEC 1 ISO P0 |
| Maximum Capacity / Filling Slot | No |
| Rolling Element | Ball Bearing |
| Snap Ring | Yes |
| Internal Special Features | No |
| Cage Material | Steel |
| Internal Clearance | C3-Loose |
| Inch - Metric | Metric |
| Long Description | 20MM Bore; 52MM |



AMERICAN BEARING MFG.CORP.

| | |
|--------------------------|---|
| | Outside Diameter; 15MM Outer Race Diameter; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; Yes Snap Ring; No Internal Special Features |
| Category | Single Row Ball Bearing |
| UNSPSC | 31171504 |
| Harmonized Tariff Code | 8482.10.50.68 |
| Noun | Bearing |
| Keyword String | Ball |
| Manufacturer URL | http://www.ntnamerica.com |
| Manufacturer Item Number | 6304ZZNR/2A |
| Weight / LBS | 0.317 |
| Outside Diameter | 2.047 Inch 52 Millimeter |
| Outer Race Width | 0.591 Inch 15 Millimeter |
| Bore | 0.787 Inch 20 Millimeter |
| bore diameter: | 20 mm |
| precision rating: | ISO Class 0 |
| outside diameter: | 52 mm |
| finish/coating: | Uncoated |
| overall width: | 15 mm |
| bearing material: | High Carbon Chrome Steel |
| bore type: | Round |
| cage material: | Steel |
| closure type: | Double Shielded |
| inner ring width: | 15 mm |
| row type & fill slot: | Single Row Non-Fill Slot |
| outer ring width: | 15 mm |
| snap ring included: | With Snap Ring |
| maximum rpm (grease): | 14000 rpm |
| internal clearance: | CN |
| fillet radius: | 1.1 mm |
| | |



AMERICAN BEARING MFG.CORP.

| | |
|------------------------------|----------------------------|
| operating temperature range: | -40 to 120 ° C |
| maximum rpm: | 17000 RPM |
| dynamic load capacity: | 15900 N |
| series: | 63 |
| static load capacity: | 7900 N |
| manufacturer product page: | Click here |